



LIMITED WARRANTY  
**2** YEAR | **NO** HOUR LIMIT

OR

LIMITED WARRANTY  
**5** YEAR | **500** HOUR

# SUPER Z<sup>®</sup>

**HIGH-PERFORMANCE ZERO-TURN WITH UNSURPASSED STRENGTH, RELIABILITY, SPEED, PRODUCTIVITY AND A WARRANTY TO MATCH**

## HIGHLIGHTS

- 54", 60", 66" or 72" VX4<sup>®</sup> deck technology – clean cut, excellent performance in all conditions
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak<sup>™</sup> steering – responsive, precise control
- Patented automatic parking brake
- 14 mph – gets the job done fast!
- Unmatched hydraulics – oil shuttle and cooler separates it from the competition



LIMITED  
**LIFETIME WARRANTY**  
FRAME & LEADING EDGE OF DECK

<b>ENGINE</b>	
Manufacturer	Kawasaki FX850V, FX1000V Kohler 824EFI
HP	54", 60" deck: 27HP - FX850 72" deck: 35HP - FX1000 54", 60" deck: 29HP - Kohler 824 EFI 66", 72" deck: 33HP - Kohler 824 EFI * Per SAE J1995
Displacement	FX850: 852cc FX1000: 999cc 824 EFI: 824cc
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	3 year
<b>DRIVE SYSTEM</b>	
Type	Dual hydrostatic
Pumps	21cc Hydro-Gear PY pumps
Wheel Motors	Parker TG310
Hydraulic Lines	Stainless steel Parker seal loc technology
Hydraulic Cooling	Oil cooler with 8" fan
Reservoir Capacity	3 gallons
Speed	14 mph
Parking Brakes	Patented automatic
<b>DECKS</b>	
Cutting Width	Side discharge: 54", 60", 66", 72" Rear discharge: 60", 72"
Cutting Heights	1" - 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	54" deck: 3 - 18.5" x 2.5" x .20" 60" deck: 3 - 20.5" x 3.0" x .25" 66" deck: 3 - 22.5" x 3.0" x .25" 72" deck: 3 - 24.5" x 3.0" x .25"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	11 ga.+ 11 ga.+ 7 ga. welded steel

Spindle Mounts	Reinforced 11 ga. doubler + 7 ga. tripler, steel
Impact/Trim Areas	1.5" x .375" steel bar protector

<b>CONSTRUCTION</b>	
Frame	1.5" x 3.0" x .187" steel
Front Caster Wheels	Mounted with sealed ball bearings
Front Caster Forks	Fabricated 1/2" steel

<b>GENERAL</b>	
Seat	Bolstered Grammer suspension seat
Fuel Capacity	12 gallons
Cup Holder	Yes
Front Tire	13 x 6.5 - 6
Drive Tire	54" deck: 24 x 9.5 - 12 60", 66", 72" deck: 24 x 12 - 12

<b>DIMENSIONS</b>		
Weight	54": 1491 lbs 60": 1511 lbs	66": 1560 lbs 72": 1588 lbs
Height w/ rops up	71.5"	
Height w/ rops Folded	54"	
Length	54", 60" deck: 84.5" 66" deck: 85" 72" deck: 86.7"	
Width w/ chute up	54" deck: 60" 60" deck: 66"	66" deck: 72" 72" deck: 78"
Tire Width	54", 60" deck: 57" 66", 72" deck: 60"	

<b>PRODUCTIVITY*</b>		
Acres Per Hour	54": 6.11 66": 7.46	60": 6.78 72": 8.14

<b>OPTIONAL ACCESSORIES</b>	
	3-bag grass catcher (12 bushels)
	BacVac grass catcher (10 bushels)
	Mulch kit
	LED lights
	Semi pneumatic front tires
	FlexForks
	Steering extension kit
	Sand kit
	Deck rear anti-scalp wheels
	Deck stripe kit
	Electric deck lift
	Beacon kit
	Flasher kit
	Isolator grammer seat
	High vacuum deck kit

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.